



GCC JAGUAR V VINYL CUTTER 72" FOR PPF, TINT, & VINYL. (J5-183LX)

STOCK PHOTO (NOT GCC)

- Compatible with Windows 7 and above & MAC OS X 10.6 and above.
- The specification and data sheet may vary with different materials used. In order to obtain the best output quality, please maintain the machine regularly and properly.
- GCC reserves the right to change the specifications at any time without notice.

2 YEAR MANUFACTURE WARRANTY

INCLUDES STAND & BASKET

\$4381.00 (DOES NOT INCLUDE SHIPPING COST)



GCC J5-183LX

Plotter Specs

Jaguar V Series	J5-61	J5-101	J5-132	J5-163	
	J5-61LX	J5-101LX	J5-132LX	J5-163LX	J5-163LX
Operational Method	Roller-Type				
Max. Cutting Width	610 mm (24 in.)	1016mm (40 in.)	1320mm (52 in.)	1627 mm (64 in.)	1830mm (72 in.)
Max. Media Loading Width	770mm (30.3 in.)	1270mm (50 in.)	1594mm (62.7 in.)	1782mm (70.2 in.)	1990mm(78.3 in.)
Min. Media Loading Width	50 mm (1.97 in.)				
Number of Pinch Rollers	3	4		6	
Acceptable Material Thickness	0.8 mm (0.03 in.)				
Driver	DC Servo Control				
Max. Cutting Force	600g				
Max. Cutting Speed	1530 mm/sec (60 ips) (at 45° direction)				
Acceleration	4.2 G (gravity)				
Offset	0-10 mm (with an increase of 0.025mm)				
Memory Buffer	32 MB /16 MB (when using AAS)				
Interfaces	USB 2.0 (Full Speed) and Serial (RS-232), and Ethernet				
Type of Command	HP-GL, HP-GL/2				
Mechanical Resolution	0.006 mm				
Software Resolution	0.025 mm				
Distance Accuracy	±0.254 mm or ±0.1% of move, whichever is greater				
Repeatability	±0.1 mm				
Automatic-Aligning System	Available on Jaguar V LX models, including Segmental Positioning and Auto Rotation functions				N/A
Auto Rotation	Available on Jaguar V LX models				
Section Cutting	Yes				
Curve & Arc Smoothing	Yes				
Configurable Origin	Yes				
Test Cut Capability	Yes				

Test Cut Capability		Yes				
Tangential Mode		Yes				
Over Cut		Yes				
Repeat		Yes				
Copy		Yes				
Control Panel		LCD (20 digits x 2 lines), 14 Keys, 1 Power LED				
Diameter of Blade		2.5 mm				
Stand		Optional	Standard			
Media Basket		Optional				
Power Supply		100-240 VAC 50 / 60 Hz (auto switching)				
Power Consumption		Max. 250 W				
Dimension	(H x W x D) mm	412 * 950 * 486	1096 * 1450 * 651	1111 * 1774 * 651	1127 * 1962 * 756	1127 * 2170 * 756
	(H x W x D) in	16.2 * 37.4 * 19.1	43.1 * 57 * 25.6	43.7 * 69.8 * 25.6	44.4 * 77.2 * 29.8	44.4 * 85.4 * 29.8
Net Weight		18 kg/ 39.6 lb	41.5 kg/ 91.4 lb	50 kg/ 110.2 lb	69 kg/ 152.119 lb	88 kg/ 194.0068 lb
Operation Environment	Temperature	15° C-30° C / 60°F-86° F				
	Humidity	25% ~ 75%				

- Compatible with Windows 7 and above & MAC OS X 10.6 and above. (*Purchasing serial number for "Sure Cuts A Lot" software to work with Mac OS.)
- The specification and data sheet may vary with different materials used. In order to obtain the best output quality, please maintain the machine regularly and properly.
- GCC reserves the right to change the specifications at any time without notice.
- GCC certified material in tracking is Avery MPI 3000.
- The above listed specification values are effective only when operated with media certified by GCC.



CALL US FOR MORE INFORMATION OR TO ORDER TODAY.

PHONE—800-223-4385
 info@sagrproducts.com

SAGR Products Int'l

* ALL LISTED ITEMS DO NOT INCLUDE SHIPPING FEES. THE PLOTTERS REQUIRE PAYMENT AT TIME OF ORDER, PLOTTERS ARE SHIPPED DIRECT TO THE BUYER AND ARE DELIVERED BY FREIGHT TRUCK. THE ACCESSORIES SHIP STANDARD UPS SERVICE.